

BEA-200 Extraction arm



Description

Extraction arm that is suitable for the wide range of applications where the extraction and removal of large amounts of welding fumes and fine dust at source is required.

Industries and applications

- Metalwork
- Automotive
- Food industry
- Precision engineering
- Shipbuilding

Features

- Free flow ducts
- Pneumatic cylinder support
- Increased airflow capacity
- Built-in damper
- Robust design
- Wide selection of different types

Article numbers / Technical characteristics

Article №	Model	Reach area, m	Ø Diameter, mm	Recommended airflow, m³/h	Installation height, m
5311	BEA-200-2S	2	200	1000-2000	1-2
5312	BEA-200-3S	3			
5313	BEA-200-4S	4			
5314	BEA-200-2H	2			2
5315	BEA-200-3H	3			2-3
5316	BEA-200-4H	4			2
5317	BEA-200-2HF	2			2-3
5318	BEA-200-3HF	3			
5319	BEA-200-4HF	4			

Delivery set / Mountings

Model	Type of mounting	Delivered with
BEA-200-2S	Without bracket (as standard): - DCSC-M-2 filters only	
BEA-200-3S		
BEA-200-4S		
BEA-200-2H	With bracket (standard): - wall	Bracket; Connection hose (Ø 200); 2 x Hose clamp (Ø 200);
BEA-200-3H		
BEA-200-4H		
BEA-200-2HF	Without bracket (as standard): - DCSC-W-200 filters only	
BEA-200-3HF		
BEA-200-4HF		

Pressure drop diagramm

